

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
22 July 2004 (22.07.2004)

PCT

(10) International Publication Number
WO 2004/061759 A2

(51) International Patent Classification⁷: **G06K 11/00**

(21) International Application Number:
PCT/GB2003/005701

(22) International Filing Date:
31 December 2003 (31.12.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0300291.2 7 January 2003 (07.01.2003) GB
0318121.1 1 August 2003 (01.08.2003) GB

(71) Applicant (for all designated States except US): **SENSOPAD TECHNOLOGIES LIMITED** [GB/GB];
Harston Mill, Harston, Cambridgeshire CB2 5GG (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **SILLS, Colin, Stuart** [GB/GB]; Sensopad Technologies Limited, Harston

Mill, Harston, Cambridgeshire CB2 5GG (GB). **KREIT, Darran** [GB/GB]; Sensopad Technologies Limited, Harston Mill, Harston, Cambridgeshire CB2 5GG (GB). **HOWARD, Mark, Anthony** [GB/GB]; Sensopad Technologies Limited, Harston Mill, Harston, Cambridgeshire CB2 5GG (GB).


(74) Agents: **BERESFORD, Keith, Denis, Lewis et al.**; Beresford & Co, 16 High Holborn, London WC1V 6BX (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,

[Continued on next page]

(54) Title: SENSING APPARATUS AND METHOD



(57) Abstract: There is described a sensing apparatus comprising first and second members which are supported relative to each other by a support means. The first member comprises a magnetic field generator for generating a magnetic field and the second member comprises an aerial for monitoring the magnetic field generated by the magnetic field generator. At least one of the first and second members is locally deformable relative to the other of the first and second members in order to vary at least one of the magnetic field generated by the magnetic field generator and the electromagnetic coupling between the magnetic field generator and the receive aerial so that, in response to a local deformation, a signal is induced in the receive aerial indicative of the position of the local deformation.